




ACIDO DODECILBENZESOLFONICO

Technical Data Sheet No. 4003 – February 2019



Product Description

SOLFODAC AC-3-H is the sulphonic acid of HYBLENE 113 linear alkyl benzene. It is manufactured in Terranova dei Passerini (Lodi, Italy) plant. The chemical structure is the following:



CAS registry no. 85536-14-7
 EINECS no. 287-494-3

Sales Specification

Property	Test Method	Unit	Guaranteed Value ¹
√ Appearance at 25°C	ASTM E284	-	liquid
√ Anionic active matter (MW = 320)	ASTM D3049	% mass	≥ 96,5
√ Unsulphonated matter	EN 13273	% mass	≤ 2,5
√ Sulphuric acid	ISO 6844	-	≤ 1,2
√ Colour (5% m/v in Isopropanol)	EN 1557	Klett	≤ 40
√ Water (Karl-Fischer)	EN 13267	% mass	≤ 0,5

√ value reported on inspection certificate.

¹ specification No. 7050 rev. 4 of December 22nd, 2015.

Additional Properties

Property	Test Method	Unit	Typical Value
Total 2-Phenyl Isomer (+)	RCM 1103	% mass	30
Viscosity at 20°C	ASTM D445 / ASTM D7042	cSt	1.077
Viscosity at 30°C	ASTM D445 / ASTM D7042	cSt	650
Density at 20°C	ASTM D7042 / ASTM D4052	kg/m ³	1.049
Density at 30°C	ASTM D7042 / ASTM D4052	kg/m ³	1.040
Flash point	ASTM D 93	°C	> 125

(+) value determined on raw material HYBLENE 113

RCM and MPL are Sasol Italy analytical methods, internal or referred to international standard. Additional information available upon request.



ACIDO DODECILBENZESOLFONICO

Technical Data Sheet No. 4003 – February 2019

Main Applications

ACIDO DODECILBENZESOLFONICO is an intermediate for the production of the anionic surfactant, linear alkyl benzene sulphonate sodium salt.

In detergency field the sodium salt of ACIDO DODECILBENZESOLFONICO is used as high performance anionic surfactant in Heavy Duty Liquid, Heavy Duty Powder, Hand Dish Washing and Industrial Degreasing formulations. ACIDO DODECILBENZESOLFONICO salts is used as surfactant for Enhanced Oil Recovery at high temperature.

Handling and Storage : ACIDO DODECILBENZESOLFONICO should be stored preferably in stainless steel tanks or plastic receptacles.

ACIDO DODECILBENZESOLFONICO must be stored at temperature below 40°C and avoid exposure to light in order to minimise hydrolysis and darkening phenomena.

Storage tanks must be heated with water warmed at a temperature below 50°C. The use of steam to warm up the product is absolutely prohibited.

ACIDO DODECILBENZESOLFONICO is a viscous liquid and soluble in water at room temperature.

Shelf-life is 7 months from production date for product in its original and sealed packaging.

Packaging

ACIDO DODECILBENZESOLFONICO is generally supplied in plastic drums, details on available packaging can be obtained from sales department.

Data regarding safety, transport classes, toxicology and biodegradability of the product can be obtained from the corresponding material safety data sheet.

This information is based on our present knowledge and experience. but it is not a guarantee of the performance of our products since the conditions of use are not under our direct control.

However, it implies no liability or other legal responsibility on our part, including any existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. All our business transactions shall be governed exclusively by our General Sales Conditions.

Sasol is a registered trademark of Sasol Ltd. Product trademarks displayed in this document are the property of the Sasol Group of Companies. Users of this document are not permitted to use these trademarks without the prior written consent of their proprietor. All rights not expressly granted are reserved.