# BLUESIL TM FLD 47 V 5 000 to 47 V 1 000 000



# distribuito da: ANDREA GALLO DI LUIGI S. r. l.

azienda fondata nel 1892

Via Erzelli, 9 - 16152 Genova (Italy) Tel. 010.650.29.41

www.andreagallo.it

# High Viscosity Silicone Oils

# **Description**

**BLUESIL FLD 47 V 5 000 to 47 V 1 000 000** (viscosities 5 000 - 10 000 - 12 500 - 30 000 - 60 000 - 300 000 - 500 000 - 1 000 000) are dimethylpolysiloxane polymers with linear chains.

Refer to the regulatory attestation for the conformance to any regulated applications

# Examples of applications

#### BLUESIL FLD 47 V 5 000 to 47 V 1 000 000 can be used as:

- · Antiadherent agents: mould release of plastics and metal castings,
- · Lubricants: lubrication of elastomers and plastics on metal,
- · Hydraulic damping fluids,
- Additives in maintenance products (wax polishes, floor and furniture polishes...).

Warning: It is the sole responsibility of the user to select the product in the BLUESTAR SILICONES range that meets any requirements for their applications

## **Advantages**

- Excellent thermal stability.
- Good resistance to combustion.
- Good dielectric properties.
- Low freezing point.
- Low surface tension.
- High compressibility.
- Good oxidation resistance.
- Absence of ageing under exposure to weather conditions.
- Low variation of viscosity with temperature.
- Good shear resistance.
- Non miscible with most of organic materials.
- Soluble in aromatic, aliphatic and chlorinated solvents.
- Insoluble in water and alcohols.

# Characteristics

Appearance	
Viscosity at 25°C, mm <sup>2</sup> /s, approx	5 000 to 1 000 000
Density at 25°C, approx	0.973
Flash point (open cup), °C	> 300
Fire point, °C	> 350
Pour point, °C, approx	45
Refractive index at 25°C, approx.	1.404
Surface tension at 25°C nN/m, approx	21.1
Vapour tension at 200°C, Pa, approx	1.33



# BLUESIL<sup>TM</sup> FLD 47 V 5 000 to 47 V 1 000 000



# distribuito da: ANDREA GALLO DI LUIGI S. r. l.

azienda fondata nel 1892 Via Erzelli, 9 - 16152 Genova (Italy) Tel. 010.650.29.41

	www.andreagallo.it	
Characteristics (cont')	Expansion coefficient between 25°C and 100°C, cm³/cm³, °C, approx9.45 10-4	
	Specific heat between 40°C and 200°C:	
	- J/g°K, approx1.50	
	- Cal/g°K, approx0.36	
	Thermal conductivity, W/m°K, approx 0.16	
	Viscosity / temperature coefficient (1), approx	
	Dielectric strength at 25°C, kV/mm, approx18	
	Permittivity at 25°C, approx	
	Dielectric dissipation factor tg at 25 °C and 100 kHz, approx1. 10 <sup>-4</sup>	
	Volume resistivity at 25°C, Ω.m , approx1.10 <sup>15</sup>	
	(1) Viscosity / temperature coefficient = 1 _ <u>Viscosity at 99 °C</u>	
	Viscosity at 38 °C	
Packaging	BLUESIL FLD 47 V 5 000 to 47 V 1 000 000 are supplied in 25 kg, 200 kg drums, in 1000 kg containers or in tankers.	
Storage and shelf life	When stored in their original packaging at a temperature of between -20°C et +50°C, <b>BLUESIL FLD 47 V 5 000 to 47 V 1 000 000</b> may be stored for up to 36 months from their date of manufacture.	
	Comply with the storage instructions and expiry date marked on the packaging.	
	Beyond this date, Bluestar Silicones no longer guarantees that the products meet the sales specifications.	
Safety	Consult the Safety Data Sheets of <b>BLUESIL FLD 47 V 5 000 to 47 V 1 000 000</b> .	

Visit our website www.bluestarsilicones.com



Bluestar Silicones France 21 Avenue Georges Pompidou F69486 Lyon Cedex 03 **FRANCE** Tel. (33) 4 72 13 19 00 Fax (33) 4 72 13 19 88



## NORTH AMERICA

Bluestar Silicones USA 2 Tower Center Boulevard Suite 1601 East Brunswick, NJ 08816-1100 **United States** Tel. (1) 732 227-2060 Fax. (1) 732 249-7000



#### A LATIN AMERICA

Bluestar Silicones Brazil Ltda. Av. Maria Coelho Aguiar, 215 Bloco G - 1°andar 05804-902-Sao Paulo - SP-Tel. (55) 11 37477887



## ASIA PACIFIC

Bluestar Silicones Hong Kong Trading Co. Ltd 29th Floor, 88 Hing Fat Street Causeway Bay Hong Kong Tel. (852) 3106 8200 Fax (852) 2979 0241

# Warning to the users

The information contained in this document is given in good faith based on our current knowledge. It is only an indication and is in no way binding, particularly as regards infringement of or prejudice to third party rights through the use of our products. BLUESTAR SILICONES guarantees that its products comply with its sales specifications. This information must on no account be used as a substitute for necessary prior tests which alone can ensure that a product is suitable for given use. Users are responsible for ensuring compliance with local legislation and for obtaining the necessary certifications and authorisations. Users are requested to check that they are in possession of the latest version of this document and BLUESTAR SILICONES is at their disposal to supply any additional information.

